



## Spring Clips

Material: Spring Steel - ASTM-A684

Standard Plating: Cadmium-Yellow Chromate AMS QQ-P-416 CLASS 2 TYPE II

Other Finishes Available: [www.atlee.com/wp-content/uploads/docs/finishes.pdf](http://www.atlee.com/wp-content/uploads/docs/finishes.pdf)




Figure 1. Figure 2.

### .625 Diameter Spring Clips – Spring Steel

Part #	Nom Dia	Min Dia	Max Dia	Holes	U +/- .010	A +/- .020	B +/- .010	C +/- .020	W +/- .003	V +/- .003	S +/- .010	X +/- .020	X +/- .020	T +/- .005	T1 +/- .005	Slots	Figure
100-200-10A-000	0.625	0.585	0.655	3	2	0.768	0.674	0.41	0.022	0.128	0.25			1.5	0.75	0	1
100-200-10A-001	0.625	0.585	0.655	2	1	0.768	0.674	0.41	0.022	0.128	0.188			0.625		0	1
100-200-10A-002	0.625	0.585	0.655	2	1	0.76	0.656	0.41	0.014	0.115	0.25			0.5		0	1
100-200-10A-003	0.625	0.585	0.655	2	0.75	0.76	0.656	0.41	0.014	0.099	0.188			0.375		0	1
100-200-10A-004	0.625	0.585	0.655	3	1	0.76	0.66	0.41	0.016	0.07	0.188			0.625	0.312	0	1
100-200-10A-005	0.625	0.585	0.655	3	1.625	0.76	0.66	0.41	0.016	0.128	0.25	0.52	0.52	1.125	0.562	2	2
100-200-10A-006	0.625	0.585	0.655	1	0.75	0.76	0.656	0.41	0.014	0.098	0.375					0	1
100-200-10A-007	0.625	0.585	0.655	2	0.75	0.76	0.656	0.41	0.014	0.099	0.188			0.375		0	1
100-200-10A-008	0.625	0.585	0.655	2	0.75	0.76	0.656	0.41	0.014	0.099	0.188	0.125	0.125	0.375		4	2
100-200-10A-009	0.625	0.585	0.655	1	0.375	0.76	0.66	0.41	0.016	0.098	0.188					0	1
100-200-10A-010	0.625	0.585	0.655	2	1	0.76	0.656	0.41	0.014	0.136	0.175	0.48		0.65		1	2
100-200-10A-011	0.625	0.585	0.655	2	1.375	0.76	0.656	0.41	0.014	0.136	0.312	0.67		0.75		1	2
100-200-10A-012	0.625	0.585	0.655	2	0.75	0.76	0.656	0.41	0.014	0.103	0.156			0.437		0	1
100-200-10A-013	0.625	0.585	0.655	2	1.375	0.76	0.656	0.41	0.014	0.103	0.312	0.67		0.75		1	2
100-200-10A-014	0.625	0.585	0.655	1	0.5	0.76	0.656	0.41	0.014	0.128	0.25					0	1
100-200-10A-015	0.625	0.585	0.655	2	0.75	0.76	0.656	0.41	0.014	0.125	0.187	0.1	0.1	0.375		5	2
100-200-10A-016	0.625	0.585	0.655	2	1	0.76	0.66	0.41	0.016	0.14	0.187			0.625		0	1
100-200-10A-017	0.625	0.585	0.655	3	1.688	0.76	0.656	0.41	0.014	0.128	0.218			1.25	0.625	0	1
100-200-10A-018	0.625	0.585	0.655	3	1	0.76	0.656	0.41	0.014	0.136	0.187			0.625	0.312	0	1
100-200-10A-019	0.625	0.585	0.655	2	1.875	0.76	0.656	0.41	0.014	0.103	0.234	0.6	0.6	1.4		2	2
100-200-10A-020	0.625	0.585	0.655	2	0.5	0.76	0.656	0.41	0.014	0.093	0.125			0.25		0	1
100-200-10A-021	0.625	0.585	0.655	3	1.625	0.76	0.656	0.41	0.012	0.128	0.25			1.125	0.562	0	1

**Note:** All dimensions are with clip secured to flat surface as normally mounted with component of nominal diameter in place.