



Spring Clips

Material: # 172 Beryllium Copper ASTM B194

Standard Plating: Cadmium-Yellow Chromate AMS QQ-P-416 CLASS 2 TYPE II

Other Finishes Available: www.atlee.com/wp-content/uploads/docs/finishes.pdf




Figure 1. Figure 2.

.391 Diameter Spring Clips - Beryllium Copper

Part #	Nom Dia	Min Dia	Max Dia	Holes	U +/- .010	A +/- .020	B +/- .010	C +/- .020	W +/- .003	V +/- .003	S +/- .010	X +/- .020	X +/- .020	T +/- .005	T1 +/- .005	Slots	Figure
100-300-06A-000	0.391	0.361	0.401	2	0.625	0.48	0.43	0.27	0.016	0.093	0.156			0.312		0	1
100-300-06A-001	0.391	0.361	0.401	2	0.625	0.48	0.43	0.27	0.016	0.103	0.156			0.312		0	1
100-300-06A-002	0.391	0.361	0.401	2	0.625	0.48	0.43	0.27	0.018	0.093	0.156			0.312		0	1
100-300-06A-003	0.391	0.361	0.401	2	0.625	0.48	0.43	0.27	0.018	0.103	0.156			0.312		0	1
100-300-06A-004	0.391	0.361	0.401	2	0.625	0.48	0.43	0.27	0.018	0.128	0.156			0.312		0	1
100-300-06A-005	0.391	0.361	0.401	1	0.25	0.48	0.43	0.27	0.018	0.093	0.125					0	1

Note: All dimensions are with clip secured to flat surface as normally mounted with component of nominal diameter in place.